



suitable
FOR EVERY MATERIAL
& THICKNESS

SUITABLE FOR EVERY
**installation
scenario**

Time-saving
BY EASY ASSEMBLY



LED feedback
TEMPERATURE
& FLOW RATE

TWINLEVEL^o TLI Quick Assembly PATENT PENDING

THE EASY-TO-USE AND EASY-TO-INSTALL OPERATING DEVICE

TLI Quick Assembly is a compact user interface for TLC mixing and flow valves in kitchen fixtures, bathroom sinks, showers, and bathtubs.

Installation is extremely straightforward thanks to the patented assembly sleeve. It can be quickly and effortlessly installed on every kind of surface, from stainless-steel exterior to concrete wall, thus making small drill holes, screws, and mounting plates a thing of the past.

Plus, each and every TLC function is accessible. The push button can be turned to adjust the temperature setting or simultaneously pressed and turned to regulate the flow rate. Three programmable quick access settings for temperature and flow rate make the user's favorite settings available in an instant. The LED ring provides subtle visual feedback, while integrated scalding protection ensures maximum safety.

RAPID INSTALLATION

The assembly sleeve makes installation quick and effortless

EASY TO USE, CONVENIENT, AND HYGIENIC

Reliably effortless operation, hygiene functions, and a wide range of settings

VISUAL FEEDBACK

LED ring allows for visualization of the temperature and flow rate

QUICKACCESS

Three temperature settings and programmable flow rate

INTEGRATED SCALDING PROTECTION

Gradual increase to temperatures greater than 40°C

HOLE DIAMETER

Ø 30mm

COMPATIBILITY

TLC Temperature, TLC Double, TLC Compact

Oblamatik AG
La-Nicca-Strasse 12
CH-7000 Chur

P +41 81 553 53 00
sales@oblamatik.ch
oblamatik.ch

